Emergency SAMCOM SLM18T - 2 1x8W Fluorescent







Emergency SAMCOM SLM18T - 2 1x8W Fluorescent adalah pictogram menunjukan lokasi pintu darurat, jika terjadi kebakaran/keadaan darurat lainnya

Rating: Not Rated Yet
Ask a question about this product

ManufacturerSamcom

Description

Emergency SAMCOM SLM18T - 2 1x8W Fluorescent adalah pictogram menunjukan lokasi pintu darurat, jika terjadi kebakaran/keadaan darurat lainnya.

Sebuah lampu darurat adalah perangkat pencahayaan dilengkapi baterai yang otomatis menyala ketika sebuah bangunan mengalami pemadaman listrik.

Tanda keluar dirancang agar benar-benar jelas dan dapat dimengerti oleh siapa saja, umumnya berarti rambu keluar yang menunjukkan kata "EXIT" atau padanannya dalam bahasa lokal.

Baca juga produk serupa lainnya Lampu Exit Samcom SLR158 Single Double.

Cocok digunakan sebagai lampu untuk:

- sebagai tanda keluar gedung perkantoran,
- untuk area pabrik dan gudang,
- banyak dipakai untuk lampu emergency exit mall terkemuka di perkotaan,
- cocok dipakai untuk stasiun angkutan umum,
- dan berbagai kebutuhan lainnya sesuai fungsi dan kegunaan.

Spesifikasi produk Emergency SAMCOM SLM18T:

1. INPUT VOLTAGE : 230Vac 50/60Hz ± 10% or 115Vac 50/60Hz ± 10% or others
2. BATTERY : 2.4V 2.5AH/4.5AH High temp rated Nickel Cadmium cells or others
3. LAMP USED : Fluorescent tube 1 x 8W daylight 30cm
4. RATED PERIOD : > 2 hrs, 3 hrs or others
5. MODE : Maintained
6. OPERATION TEMPERATURE: ta 40 ºC
7. POWER CONSUMPTION : < 12VA
8. CHARGE MONITOR : Super bright green LED 5mm Ø
9. RECHARGE PERIOD : 16 ~ 24 hrs
10. EMERGENCY LUMINANCE : > 8 cd/m2
11. ELECTROMAGNETIC FIELD : 9.5m gause @ 0.1m
12. CHARGER : Hybrid controlled charger
13. PROTECTION : Low volt cut-off to prevent battery over discharge, Incoming AC fuse and Battery DC fuse, Tropical climate protection coating on hybrid control circuit
14. CONSTRUCTION : Electrode galvanised sheet steel with epoxy powder coating, 20mm Ø K/O hole, Fire Retardant Acrylic Opal diffuser
15. DIMENSION : 395mm(L) x 60mm(W) x 267mm(H)
16. WEIGHT : 2.68kg (Net) / 2.78kg (Gross)
17. PACKING : One unit per carton
18. CARTON / DIMENSION : Double wall corrugated / 430mm(L) x 70mm(W) x 290mm(H)
19. COMPLIANCE : CP 19, SS263 : Part 2, IEC 598-2-22
20. WARRANTY : 1 Year
21. ACCESSORY : Wall mounting bracket (for single face)

Reviews

There are yet no reviews for this product.